

1200

Variable-Frequency AC Drive



Overview

The 1200 provides reliable, efficient, cost-effective variable-frequency (V/Hz) or flux vector control of a wide variety of motors. It incorporates the latest technologies in insulated gate bipolar transistors (IGBTs), pulse-width modulation (PWM), and digital signal processing (DSP) to deliver optimum motor performance, complete programmability, and simplicity of operation.

Performance Flexibility

The 1200 accommodates a broad range of performance requirements. Units may be configured for constant-torque operation for heavy-duty cyclic loads, variable-torque operation for medium-duty requirements, or extended-torque operation for centrifugal loads such as fans and pumps. The drive operates in a transducerless vector control mode that does not require a feedback device and produces full torque to base speed with full starting torque. For demanding applications, an incremental encoder or resolver interface can be added for precise position, velocity, and torque regulation and improved dynamic performance. Dual- and triple-encoder interfaces are also available for position-following or dual-transducer applications. Variable-frequency control is alternately available for applications that do not require critical velocity or torque control. Several controller options are available to meet differing application requirements.

Motor-Independent Design

The 1200 can operate any standard- or inverter-duty AC induction or synchronous motor, making it ideal for retrofits and new applications alike. A unique, proprietary digital current regulator (DCR) tunes the drive continuously in real time, eliminating the usual current-loop tuning process required by conventional drives. Digital space vector (DSV) control can be selected for reduced motor noise and low current ripple.

Auto Tuning

Once routine electrical connections have been made, simple-to-use auto-tuning features adjust virtually all motor- and load-dependent parameters. No motor maps are required. Simply enter basic motor information from the nameplate, and the advanced setup routines do the rest. The drive is completely tuned within minutes.

Application Software

A wide variety of software options is available to tailor the 1200 to an application, from a fully featured velocity/torque control for general purposes to a host of powerful programs pre-engineered for specific applications. Customization is possible with many programs using UEdit®, a Windows-based programming tool that lets users extend an application using IEC 1131 standard ladder diagrams and function blocks.

Digital Setup, Easy Operation

A keypad and liquid crystal display provide a simple interface for setting and viewing operating parameters and diagnostics. All controller settings are made digitally for precision and repeatability. Readouts and fault messages are displayed in readily understandable language. An optional graphic display provides a variety of visual formats for accessing drive information.

1200

Variable-Frequency
AC Drive

Overview **Multiaxis and Tandem Operation**

(continued)

A built-in high-speed synchronous communication port allows the motion of multiple slave drives to be precisely coordinated. With optional master/slave software, the velocity ratio and position phasing of the drives can also be controlled. Multiple motors can be operated in parallel from a single drive using variable-frequency control. Two drive sections can be operated in tandem for high-power applications.

Power Quality

A unique bus architecture provides near-unity overall power factor and low harmonic line currents at all motor speeds. High-power units also offer a six-phase (12-pulse) configuration for a single drive section and a twelve-phase (24-pulse) configuration for a tandem drive for minimizing line harmonics in critical applications.

Protection and Advanced Diagnostics

The 1200 monitors its operating conditions and provides a comprehensive set of overload, short circuit, and other electronic protective features to ensure safe, reliable operation. Faults indications are displayed in plain language. A log maintains a history of fault occurrences and externally triggered events.

Communications

A fully isolated RS-422/485 serial interface is provided for connecting the drive to a process controller, communication network, or programmable controller. A variety of popular communication protocols is available through software or optional Anybus modules. Optional Bluetooth and MaxStream modules provide short- and long-range wireless communications. An RS-232 connection is also provided for connecting a personal computer. Windows-based PCs can set up, monitor, and control a network of drives using optional UEdit® software. The Drive Talk™ app provides remote interface capabilities for the iPhone and iPad.

Packaging

Compact and rugged, the 1200 is available either enclosed or as an open chassis for mounting inside an enclosure. Both versions can be foot-mounted to a wall or subplate or flange-mounted through a cutout to dissipate heat outside an enclosure.

Features & Benefits

General

- 24-bit digital signal processor (DSP) for fast processing
- 512 kilobytes battery backup memory for application setup data
- 1.5 megabytes scratch pad memory and 6.0 megabytes firmware memory
- Clock/calendar maintains accurate time during power outage
- Sine-coded PWM waveform output for improved torque performance
- High-switching-frequency IGBT devices for smooth, quiet operation
- Digital current regulator for high-speed operation and fast response
- Digital space vector control for reduced motor noise and low current ripple
- Flux vector control for full starting torque and full torque to base speed
- Variable-frequency operation for simple control of motor speed
- Internal control loop for maintaining speed with sudden load changes
- Automatic field weakening for speeds up to three times base speed
- Unique architecture for high power factor and low total harmonic distortion
- Integral dynamic braking for fast deceleration or energy absorption
- Power disturbance ride-through for reducing nuisance trips
- User-programmable analog and digital inputs and outputs
- Through-hole heat sink mounting of chassis units for dissipating heat externally
- Optional NEMA 1 (IP20) and NEMA 3R (IP23) or NEMA 4 (IP66) enclosures

Ease of Installation, Setup, and Maintenance

- Automated setup features require no chart recorders or meters
- Software calibration and adjustment eliminates tuning components
- Digital parameter adjustment for precise and repeatable settings
- Software input and output scaling eliminates potentiometers
- Complete, self-contained package requires minimal option boards
- Identical control boards across full power range reduces spare parts

Ease of Use

- Touch keypad for easy parameter adjustment and access to displays
- Two line descriptive plain-language display with numerical and bar graph readouts
- Optional graphics display for charting drive information in real time
- Comprehensive plain-language fault diagnostics with time-stamped fault log

Safe, Reliable Operation

- Extensive electronic protection circuits
- Tolerant of AC line voltage and frequency fluctuations
- S-curve acceleration reduces shock and extends equipment life
- Multilevel security code prevents unauthorized parameter changes
- Lockout of local operator controls for safe remote operation

Specifications Electrical

Input Supply

Voltage:	230, 460, or 1150 V AC nominal (200 to 240, 380 to 480, or 950 to 1200 V AC), three-phase (6-pulse); six-phase (12-pulse) available 50 hp CT and above; twelve-phase (24-pulse) available on tandem drives Phase sequence insensitive
Voltage tolerance:	–50% of nominal, +15% of nominal (1½ to 100 hp CT) –15% of nominal, +15% of nominal (above 100 hp CT)
Frequency:	47 to 63 Hz
Power factor:	Displacement: 1.00 at all loads and speeds Overall: 0.94 at rated load

Output Rating

Voltage:	Zero to input supply voltage, three-phase
Frequency:	Zero to 120 Hz for transducerless vector control Zero to 180 Hz for transducer-based vector control Zero to 300 Hz for variable-frequency control
Switching frequency:	1 to 12 kHz, programmable

Service Conditions

Efficiency:	97% nominal at rated switching frequency																
Overload current:	<table><thead><tr><th></th><th><i>Torque</i></th><th><i>Overload (1 min)</i></th><th><i>Maximum</i></th></tr></thead><tbody><tr><td>Constant</td><td>150% to 200% of rated</td><td>200% of rated</td><td></td></tr><tr><td>Variable</td><td>120% to 150% of rated</td><td>140% to 160% of rated</td><td></td></tr><tr><td>Extended</td><td>110% to 120% of rated</td><td>120% to 140% of rated</td><td></td></tr></tbody></table>		<i>Torque</i>	<i>Overload (1 min)</i>	<i>Maximum</i>	Constant	150% to 200% of rated	200% of rated		Variable	120% to 150% of rated	140% to 160% of rated		Extended	110% to 120% of rated	120% to 140% of rated	
	<i>Torque</i>	<i>Overload (1 min)</i>	<i>Maximum</i>														
Constant	150% to 200% of rated	200% of rated															
Variable	120% to 150% of rated	140% to 160% of rated															
Extended	110% to 120% of rated	120% to 140% of rated															

Environmental

Operating temperature:	Control section: –4° to 131° F (–20° to 55° C) Heat sink (standard): –40° to 104° F (–40° to 40° C) Heat sink (derated): –40° to 131° F (–40° to 55° C)
Storage temperature:	–40° to 158° F (–40° to 70° C)
Operating humidity:	95% maximum, noncondensing
Altitude:	To 3,300 ft (1,000 m) without derating

Performance

Frequency Control

Range:	Zero to base speed at full torque Base speed to 300 Hz at constant power
Resolution:	0.024% with analog input (12-bit) 0.1 Hz with digital input

Velocity Control

Range:	Zero to base speed at full torque Base speed to 180 Hz at constant power with transducer Base speed to 120 Hz at constant power without transducer
Regulation:	±0.001% of base speed, down to zero, with transducer ±0.5% of base speed, 2 Hz and above, without transducer

Torque Control

Starting torque:	Constant torque: zero to 150% of rated Variable torque: zero to 120% of rated Extended torque: zero to 110% of rated
Regulation:	±3.0% of maximum with transducer ±10% of maximum without transducer

Inputs and Outputs

Analog Inputs

Three (3) 12-bit analog inputs (±10 V DC or 0 to 20 mA)

Analog Outputs

Two (2) 12-bit analog outputs (±10 V DC and 0 to 20 mA)

Digital Inputs

Twelve (12) digital inputs (require sink of 1 mA to common)

Converter Interface Module: Provision for input converters rated 2.5 to 28 V DC @ 30 mA, 90 to 140 V AC @ 11 mA, and 180 to 280 V AC @ 5 mA

Digital Outputs

Six (6) digital outputs (open-collector drivers rated 24 V DC @ 500 mA)

Converter Interface Module: Provision for output converters rated 5 to 60 V DC @ 3 A, 12 to 140 V AC @ 3 A, or 24 to 280 V AC @ 3 A; or for normally open or normally closed relay converters rated 250 V AC @ 8 A

1200

Variable-Frequency AC Drive

Specifications **Serial Communications**

(continued)

Asynchronous

Port(s): One RS-232/422/485, isolated, and two auxiliary RS-422/485

Protocols: ANSI-x3.28-2.5-A4 or Modicon RTU, standard

Synchronous

Port: RS-485 for high-speed master/slave networking

Communication Modules

Anybus: One module provision
Options: CANopen, CC-Link, ControlNet, DeviceNet, Ethernet, Interbus, LonWorks, Modbus Plus, Profibus DPV1, Profibus Master

Bluetooth or MaxStream: 100 MHz control: one module provision
280 MHz control: two module provisions
MaxStream options: 900 MHz and 2.4 GHz

Protection

The following hardware conditions are detected. Additional protective features are provided by the application software.

- Ground fault
- Phase-to-phase short circuit
- DC bus overvoltage
- DC bus undervoltage
- Instantaneous overcurrent
- Motor overload
- Heat sink overtemperature
- Ambient overtemperature
- Power transistor fault
- Logic power undervoltage
- Memory malfunction
- Processor not running fault

Options

Transducers

A motor-mounted incremental encoder or resolver and corresponding interface may be used for highest performance. The resolver interface provides an encoder emulation for paralleling feedback to other devices. Dual- and triple-encoder options are also available for position-following or dual-transducer applications.

Expanded Analog I/O

An analog interface module may be used instead of a feedback interface to expand the analog I/O capabilities of the drive. The module provides eight additional inputs and four additional outputs.

Dynamic Braking

Dynamic braking is included on small units and is optionally available on higher-power units. Appropriately sized external braking resistors are required.

Packaged Drives

Drives may be ordered as part of a packaged system including a circuit breaker, operator devices, and additional system components mounted inside a NEMA 4 (IP66) enclosure.

Power Range

Input Voltage	Constant-Torque Applications	Variable-Torque Applications	Extended-Torque Applications
230 V AC	1 1/2-20 hp (1.1-15 kW)	2-25 hp (1.5-18 kW)	10-30 hp (7.5-22 kW)
380 V AC	1 1/2-1600 hp (1.1-1200 kW)	2-2000 hp (1.5-1500 kW)	—
460 V AC	1 1/2-1600 hp (1.1-1200 kW)	2-2000 hp (1.5-1500 kW)	10-2400 hp (7.5-1800 kW)
1150 V AC	10-250 hp (7.5-187 kW)	15-300 hp (11-225 kW)	20-400 hp (15-300 kW)

Consult factory for other powers. Other voltages require appropriate derating or adjustment of the switching frequency.

UNICO—Worldwide

United States

Corporate Headquarters

Unico, Inc.
3725 Nicholson Rd.
P. O. Box 0505
Franksville, WI
53126-0505

262.886.5678
262.504.7396 fax

www.unicous.com

Bakersfield, California
661.679.7850

New Lenox, Illinois
815.485.5775

Wixom, Michigan
248.380.7610

Austinburg, Ohio
216.387.8486

Midland, Texas
432.218.7665

Sandy, Utah
801.942.2500

Canada

Mississauga, Ontario
905.602.4677

Mexico

Tampico
52.833.217.4543

South America

Bogota, Colombia
57.1.805.2897

El Tigre, Venezuela
58.283.241.4024

Europe

Milton Keynes, England
44.1908.260000

Wilnsdorf, Germany
49.2739.303.0

Bucharest, Romania
40.728.664.830

Asia

Beijing, China
86.10.6218.6365

Osaka, Japan
81.66.945.0077



A Regal Beloit Company

All trade designations are provided without reference to the rights of their respective owners.

Specifications subject to change without notice.